

3.5Q - 3.5" Ellipsoidal Spot:

A compact, lightweight ellipsoidal spot with 3.5" dia. lenses produce a soft or sharp edge light beam and capable of using M-size steel gobo patterns to project images. Useful in cramped locations for stage lighting and displays. Housing has 4 adjustable framing shutters for beam shaping, and a slot for a gobo holder. Includes 3' cord (no plug), 4-1/8" x 4-1/8" color frame, and 36" black safety cable. Choice of 5 lens assemblies for light field angles from 18° to 48°. Not variable focus. Choice of 3 lamp sockets: (-MT) G9.5 2 pin for use with EHD series and GLC series lamps, (-HPL) for use with HPL lamps, or, on request, (-MC) mini-can socket for use with mini-candela-bra screw base lamps. ETL listed for maximum 575 watts. Black color is standard. For optional colors, change -B at end of catalog number to WH = white or SL = silver. Altman brand.

3.5Q-5-MT-B	3.5" ellipsoidal spot, black, 48°, med. 2 pin socket, 120 vac	\$ 235.20
3.5Q-6-MT-B	3.5" ellipsoidal spot, black, 38°, med. 2 pin socket, 120 vac	\$ 235.20
3.5Q-8-MT-B	3.5" ellipsoidal spot, black, 28°, med. 2 pin socket, 120 vac	\$ 235.20
3.5Q-10-MT-B	3.5" ellipsoidal spot, black, 23°, med. 2 pin socket, 120 vac	\$ 235.20
3.5Q-12-MT-B	3.5" ellipsoidal spot, black, 18°, med. 2 pin socket, 120 vac	\$ 235.20

3.5Q-5-HPL-B	3.5" ellipsoidal spot, black, 48°, HPL socket, 120 vac	\$ 235.20
3.5Q-6-HPL-B	3.5" ellipsoidal spot, black, 38°, HPL socket, 120 vac	\$ 235.20
3.5Q-8-HPL-B	3.5" ellipsoidal spot, black, 28°, HPL socket, 120 vac	\$ 235.20
3.5Q-10-HPL-B3.5"	3.5" ellipsoidal spot, black, 23°, HPL socket, 120 vac	\$ 235.20
3.5Q-12-HPL-B3.5"	3.5" ellipsoidal spot, black, 18°, HPL socket, 120 vac	\$ 235.20

Accessories for 3.5Q Ellipsoidal:

3.5Q-CFB	Color frame, black, 4-1/8" x 4-1/8", included.....	\$ 5.00
SC-36B	Safety cable, black, 36", included.....	\$ 7.00
3.5Q-DN	Black donut to sharpen image, 4-1/8" x 4-1/8" with 1.25" dia. hole	\$ 8.80
3.5Q-PH	Pattern holder for 2" dia. M-size steel patterns.....	\$ 5.60
3.5Q-SN	Black snoot for 3.5Q ellipsoidal	\$ 20.80
510-F	Clamp, light duty steel with 5/16" bolt, fits 1/4" to 1" pipe	\$ 8.80
CL-04	Clamp, med duty steel for 1-1/2" pipe.....	\$ 5.00
510	Clamp, malleable iron, with 1/2" bolt. Fits 3/4" to 1-1/2" pipe	\$ 10.40
TLA-	Track lighting adapters (factory mounted) for Altman Smart-Track and some model Lightolier, Halo, Eco, and Global lighting tracks are available.....	\$ POR
Canopy	Factory installation of spotlight installed on an electrical box canopy cover, for direct wiring.....	\$ 32.00
CoilCord	Factory Installed 2'-7' coiled cord with molded Edison plug, for display or exhibit use.....	\$ 40.00
Unistrut	Plate to attach spotlight to Unistrut or similar metal strut. Required hardware (nuts, bolts, etc.) are not included.....	\$ 20.00
	Installed male 20A stage pin plug.....	\$ 23.00
	Installed male 15A molded Edison plug.....	\$ 27.00
	Installed male 20A Twist-lock plug	\$ 27.00



#3.5Q 3" Ellipsoidal Spot
[Link to data sheet](#)



Black color frame



Black color frame



Snoot



3.5Q Gobo holder



510 Clamp



Unistrut Plate



CL-04 Clamp



510-F clamp

Lamps for 3.5Q Ellipsoidal Spot:

Cat. No.	Price	Use With	Watts	Volts	Hours	Color Temp.	Rated Lumens	Lamp Base
HPL575/115	\$ 19.00	HPL Socket	575	115	300	3250K	16,520	HPL
HPL575/115-X*	\$ 19.00		575		2000	3250K	12,360	
GLC	\$ 18.95	G9.5 socket	575	115	400	3200K	15,500	G9.5
GLA	\$ 18.95		575		1500	3100K	13,500	

* HPL lamps with -X denotes longer life versions. HPL lamps are also available in 120 volt versions for locations that have higher line voltage. 375 watt lamps for G9.5 base are also available.



GLC Lamp



HPL base lamp