

COMET Followspot:

Moderate cost, high performance followspot make this best value choice for schools and small theatre. Useful for distances of 75' to 125'. Zoom focus of 2.3° to 12.2° . Dual adjustable lenses, top mounted iris, mechanical dimmer, and framing shutters; separate zoom and focus controls; 6 color automatic changer; removable 25' power cord with Edison plug, and locking castered tripod stand with cable hook. Height adjustable from 50" to 62". Size of housing approx. 34" long x 16" high x 17" wide. Weight 94 lbs. including stand. Includes 360 watt 75 hour FLE quartz lamp.

Light Beam Angle	Distance (ft.)	50'	75'	100'	125'	150'
2.3° Spot with Iris	Beam Dia. (ft.)	2'	3'	4'	5'	6'
	Intensity (fc.)	320	142	80	51	36
7.2° Spot	Beam Dia. (ft.)	6.3'	9.4'	12.6'	15.7'	18.9'
	Intensity (fc.)	320	142	80	51	36
12.2° Flood	Beam Dia. (ft.)	10.7'	16'	21.4'	26.7'	32.1'
	Intensity (fc.)	132	59	33	21	15

#COMET Followspot with stand and FLE lamp..... \$ 1580.80
 #FLE Lamp for Comet followspot, 360 watt 75 hour, included..... \$ 15.00

LUMINATOR:

Very compact (24 inch long) model for short to medium throws has dual adjustable lenses, top mounted controls for iris, 6 color changer, mechanical dimmer, and 11.5' power cord with Edison plug. A front holder accepts standard 7-1/2" x 7-1/2" accessories. Includes FLE 360 watt lamp and locking castered tripod stand with cable hook. Height adjustable from 48" to 60". Size of housing approx. 23" long x 13" high x 12" wide. Weight is only 60 lbs. including stand. Can be shipped UPS in 2 cartons.

Light Beam Angle	Distance (ft.)	20'	40'	60'	80'	100'
1.3° Spot with Iris	Beam Dia. (ft.)	0.5'	0.9'	1.4'	1.8'	2.3'
	Intensity (fc.)	950	238	106	59	38
7.7° Spot	Beam Dia. (ft.)	2.7'	5.4'	8.1'	10.8'	13.5'
	Intensity (fc.)	950	238	106	59	38
9.3° Flood	Beam Dia. (ft.)	3.2'	6.5'	9.7'	13'	16.2'
	Intensity (fc.)	406	101	45	25	16

#Luminator Followspot with FLE lamp and stand..... \$ 1224.80
 #FLE Lamp for Luminator followspot, 360 watt, included..... \$ 15.00

1000-Q Followspot:

Popular followspot for distances of 75' to 100'. Has rear operated iris, single adjustable lens focus, and vertical shutters. Includes a 6 color changer w/dowser, integral 25' power cable with Edison plug, FEL 1000 watt lamp, and adjustable height locking castered tripod stand with cable hook. Height adjustable from 50" to 62". Size of housing approx. 40" long x 18" high x 18" wide. Weight 116 lbs. including stand.

Light Beam Angle	Distance (ft.)	25'	50'	75'	100'	125'
1.5° Spot with Iris	Beam Dia. (ft.)	0.5'	1'	1.5'	2'	2.5'
	Intensity (fc.)	650	160	72	40	26
10° Spot	Beam Dia. (ft.)	4.5'	8.5'	13'	17.5'	21.9'
	Intensity (fc.)	650	160	72	40	26
14° Flood	Beam Dia. (ft.)	6'	12'	18.5'	25'	30.71'
	Intensity (fc.)	344	86	38	22	14

#1000-Q Followspot with FEL lamp and stand..... \$ DISC
 #FEL Lamp for 1000-Q followspot, 1000 watt, included..... \$ 15.00



Comet
[Link to data sheet](#)



Luminator
[Link to data sheet](#)



#1000Q
[Link to data sheet](#)