



UV-703 Fresnel Blacklight
[Link to data sheet](#)

MHL Blacklights:

MHL blacklights use very efficient compact metal halide lamps (MHL) and a ballast to create a UV ultraviolet light source. A special glass lens is used to filter the UV to the 365nm range and to remove almost all visible light from the beam. This type of blacklight will require a time to warm up to full intensity and can not be dimmed (on/off operation only). No cooling fans for extremely quiet operation. Models are available as floodlights, adjustable lens PAR spots, variable focus beam Fresnel spot, and long throw ellipsoidal reflector framing spot.

Professional quality for architectural, display, events, theme parks, and theatrical applications.

UV-703 10" Fresnel Blacklight:

Rugged die-cast and aluminum housing with 10" UV filter Fresnel lens and an integrated wire mesh safety screen. Front and rear focusing control for narrow spot to wide flood beam. Integrated rollers for optional barndoors. Separate magnetic ballast includes a hanging yoke and 36" power cord (no plug). Lens door has automatic safety cutoff switch to turn off lamp. Simple on/off power switch. Fixture includes safety cable, and a 25' detachable interconnect cord between the fixture and the separate ballast. Uses 450 watt MHL-450 lamp (not included). Ballast is for 120 vac 50/60 hz power or optional 208-240 vac.. Color is black. ETL and cETL listed for indoor use only.

UV-703	450 watt 10" Fresnel blacklight, black, ballast with hanging yoke, 120 vac	\$ 3318.40
UV-703-220	450 watt 10" Fresnel blacklight, black, ballast with hanging yoke, 208-240 vac	\$ 3402.40
MHL-450	Lamp for UV-703 Fresnel black light, 450 watts	\$ 67.50
F10-BD4	4 leaf barndoors for UV-703	\$ 104.80
F10-BD8	8 leaf barndoors for UV-703	\$ 126.40
F10-SN	3 in 1 snoot set for UV-703	\$ 156.00
54-5004	50' detachable interconnect cable for ballast.....	\$ 156.00
54-5005	100' detachable interconnect cable for ballast.....	\$ 256.00
510-HD	Heavy duty malleable iron pipe clamp for UV-703 housing and ballast	\$ 20.00
F-SAL	Large combination 5/8" x 1-1/8" spigot adapter for film/video stands..	\$ 33.60
F10-CB	Black hinged filter frame for UV-703	\$ 42.40

UV-150 Blacklight Outdoor PAR:

Rugged die cast and spun aluminum housing with interchangeable 8" dia. lenses has IP65 rating for outdoor or indoor use. Convection cooled. An electronic ballast is integrated into the housing. Uses an axial mounted 150 watt MHL G12 base lamp. Uses same accessories as the Outdoor-PAR64 and same lenses as the Star Par. Includes a special UV filter and clear front safety lens. Fixture includes 4' cable with bare end (no plug), set of 4 spread lenses, and safety cable. Lamp is not included. UL and CUL listed IP65 rating for 120 vac power. Black is standard.

UV-150	150 watt PAR blacklight for outdoor use, black	\$ 1424.00
MHL 150	150 watt MHL lamp for UV-150 PAR	\$ 107.25
8-CFB	Color frame, black 10" x 10", included with OD model snoots	\$ 6.40
SC-36-BK	Safety cable, 36" black, included	\$ 7.00
510-HD	Heavy duty malleable iron pipe clamp	\$ 20.00
OD-P64-SN	Combo black snoot/color frame holder, 6-3/4" long with 10" x 10" color frame	\$ 79.20
ODC-SN-Short	Combo black snoot/color frame holder, 1" long with 10" x 10" color frame.....	\$ 75.20
ODP64SNSpark	Combo black perforated (sparkle effect) snoot/color frame holder with 10" x 10" color frame	\$ 80.80



UV-150 Blacklight PAR
[Link to data sheet](#)

See following page for more blacklights and accessories



UV-250 250 Watt Blacklight Flood
[Link to data sheet](#)



UV-705 400 Watt Blacklight Flood
[Link to data sheet](#)



PHX Zoom Ellipsoidal Blacklight Spot
[Link to data sheet](#)

UV-250 Blacklight Flood:

Compact high output 250 watt blacklight flood. Convection cooled. A magnetic ballast is integrated into the housing. Uses an double ended 250 watt MHL RX7 base lamp. Includes a special UV filter and integral wire mesh safety screen. Fixture includes 5' cable with bare end (no plug), safety cable, hanging yoke, and 4 non-slip feet. Automatic safety switch cuts power if access door is opened. Lamp is not included. ETL and cETL listed for indoor use at 250 watts 120 vac 60 Hz. or 208-240 vac 60 Hz.. Uses 7-1/2" x 7-1/2" accessories. Black is standard.

Oct 1 2019 - The UV-250 Blacklight Flood is discontinued, but accessories are still available

UV-705 Blacklight Flood:

Compact high output 450 watt blacklight flood. Convection cooled. A magnetic ballast is integrated into the housing. Uses an double ended 450 watt MHL RX7 base lamp. Includes a special UV filter and integral wire mesh safety screen. Dual side mounted focus knobs adjust light beam from wide to very wide flood. Fixture includes 5' cable with bare end (no plug), safety cable, hanging yoke, and 4 non-slip feet. Automatic safety switch cuts power if access door is opened. Lamp is not included. ETL and cETL listed for indoor use at 400 watts 120 vac 60 Hz. or 208-240 vac 60 Hz.. Uses 10" x 10" accessories. Black is standard.

UV-705	450 watt blacklight flood, black, 120 vac	\$ 2432.00
UV-705-220	450 watt blacklight flood, black, 208-240 vac	\$ 2480.00
MHL-450	450 watt MHL lamp for UV-705 blacklight	\$ 67.50
510-HD	Heavy duty malleable iron pipe clamp	\$ 20.00
8-CFB	Filter frame, black 10" x 10"	\$ 5.00
SC-36-BK	Safety cable, 36" black, included	\$ 7.00
8-BD-4	4 door, 8 leaf barndoor	\$ 70.40
8-SN	Snoot	\$ 23.20

Phoenix Zoom Ellipsoidal 200 watt Blacklight:

The Phoenix PHX series zoom focus ellipsoidal framing spot housing with a compact 200 watt metal arc lamp. The lamp is integrally mounted in a glass reflector and has a life expectancy of 1500 hrs. A multi-voltage electronic ballast for the lamp is mounted on the yoke for 115 to 240 vac 60 Hz.. Rugged die cast aluminum housing features 4 shutters to shape light beam and a 2 slot accessory slot with locking closing lid can accept holders for glass or metal gobos, gobo rotator, and drop-in iris. Front holder for 7-1/2" x 7-1/2" accessories. Available as two models with lenses for 15°-35° beam or 30°-55° beam. Uses same accessories as the standard PHX series ellipsoidal spots. Standard color is black. For indoor use only. Price includes safety cable, 510 clamp, and 5' cord with bare ends (no plug). UL and CUL rated. CE rated model on request. Altman Brand.

PHXUV-1535Z	200 watt UV ellipsoidal spot, 15°-35° zoom beam, black	\$ 2012.00
PHXUV-Z3055	200 watt UV ellipsoidal spot, 30°-55° zoom beam, black	\$ 2012.00
SMR-201/UV1	200 watt reflector metal arc lamp for PHXUV spots.	\$ 561.00
510	Malleable iron pipe clamp, included.....	\$ 10.40
6-DN	Black metal donut with 3" hole to sharpen image	\$ 9.60
6-sn	Black metal snoot	\$ 16.80
PZDII	Drop-in iris to adjust light beam dia.	\$ 92.00